

ESTD. SINCE 1954



DOUBLE ACTING HYDRAULIC CYLINDERS

Technical Parameters

Model	Tonnage (T)	Stroke (mm)	Closed Height A(mm)	Extended Height B(mm)	Outside Dia (mm)	Inside Dia (mm)	Piston Dia(mm)	G.W. (kg)
HHYG-10250	10	250	380	630	70	45	36	10
HHYG-10300		300	430	730				11
HHYG-20250	20	250	390	640	80	60	45	13
HHYG-20300		300	440	740				15
HHYG-30200	30	200	364	564	95	72	65	17
HHYG-30300		300	464	764				21
HHYG-50200	50	200	374	574	120	95	70	29
HHYG-50300		300	474	774				35
HHYG-100200	100	200	389	589	175	135	90	60
HHYG-100300		300	489	789				73
HHYG-20050	200	50	217	267	228	190	135	63
HHYG-200150		150	317	467				84
HHYG-200300		300	467	767				146
HHYG-25050	250	50	261	311	270	215	180	102
HHYG-250150		150	361	511				135
HHYG-250300		300	511	811				184
HHYG-30050	300	50	280	330	285	240	200	133
HHYG-300150		150	380	530				173
HHYG-300300		300	530	830				231
HHYG-40050	400	50	341	391	325	270	220	211
HHYG-400150		150	441	591				262
HHYG-400300		300	591	891				336
HHYG-50050	500	50	376	426	372	305	250	309
HHYG-500150		150	476	626				360
HHYG-500300		300	626	92				460
HHYG-60050	600	50	397	447	402	330	270	381
HHYG-600150		150	497	647				458
HHYG-600300		300	647	947				575
HHYG-80050	800	50	438	488	472	390	320	583
HHYG-800150		150	538	688				681
HHYG-800300		300	688	988				850
HHYG-100050	1000	50	493	543	530	430	360	830
HHYG-1000150		150	593	743				970
HHYG-1000300		300	743	1043				1177

*Manufacturing Tolerance will be $\pm 10\text{MM}$

ORIENTAL TRADING CORPORATION

ISO : 9001-2008 Co

Reg. Office : 33/1, N.S Road, Marshall House,
Ground Floor, Room No. 37, Kolkata - 700 001.
Phone No. : +91-33-2230 9759, 2230 9557, 4005 5077.

Email : otccal@gmail.com